

## illbruck illmod trio

illbruck illmod trio –

illmod trio

«  
».



### illbruck illmod triplex

	Din	
	4102	B2 ( )
	52612	$\lambda = 0,048$ / •
60 70		0,8 / ( 2• ) 0,7 / ( 2• )
	EN ISO 12572	$\mu$ 100
	EN 1026	0,1 3/[ • • ( )n]
	EN1027	600
	EN ISO 717-1	45 dB 10
	18542	
		-30° - +80°
		6
		+1° - +20°

25

481-3-				
5200	60 <sup>1</sup>	5-10	9,0	36,0
5201	70 <sup>2</sup>	5-10	9,0	27,0
5202	80 <sup>3</sup>	5-10	9,0	27,0
5205	60 <sup>1</sup>	7-15	6,0	24,0

5206	70 <sup>2</sup>	7-15	6,0	18,0
5207	80 <sup>3</sup>	7-15	6,0	18,0
5210	60 <sup>1</sup>	10-20	4,5	18,0
5211	70 <sup>2</sup>	10-20	4,5	13,5
5212	80 <sup>3</sup>	10-20	4,5	13,5

1  
2  
3

DIN 7715 3  
: 58  
: 66  
: 77

## illbruck illmod trio

( .1).

illmod trio



.1

.2



.3

с ( .3)

( .2).

( )).

20°